

A

ASSISTANT COMMISSIONER FOR PATENTS
Washington, D. C. 20231

Date: December 18, 1997

Submitted herewith for filing is the patent application of Inventor(s):

Robert Sams
Richard Seidel
Michael Hopson

For: **Tripod Bearing Assembly**


Enclosed are:

- ☒ 2 sheet(s) of drawings
- ☐ A certified copy of a
- ☐ Information Disclosure Statement, PTO Form 1449, and Copies of Citations

The filing fee has been calculated as shown below for OTHER THAN A SMALL ENTITY:

FOR	NO. FILED	NO. EXTRA	RATE	FEE
Basic Fee				\$790
Total Claims	12	0	x\$ 22	\$0
Indep Claims	3	0	x\$ 82	\$0
Multiple Dependent Claims(s) Presented	0		x\$270	\$0
			TOTAL	\$790.00

- ☒ Please charge Deposit Account No. 06-1510 in the amount of \$790.00
A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated
with this communication or credit any overpayment to Deposit Account No. 06-1510.
A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees during the
pendency of this application or credit any overpayment to Deposit Account No. 06-1510.
A duplicate copy of this sheet is enclosed.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ Any filing fees under 37 CFR 1.16 for presentation of extra claims.


James J. Dottavio
Attorney or Agent of Record
Registration No. 40,360
Ford Global Technologies, Inc.
One Parklane Blvd.
911 Parklane Towers East
Dearborn, MI 48126

TRIPOD BEARING ASSEMBLY

Field of the Invention

5 The present invention relates to a tripod bearing assembly particularly for a motor vehicle.

Background of the Invention

10 Tripod bearing assemblies of the prior art include a spider with three trunions drivably engaged with an outer member to transmit torque from a first shaft to a second shaft. The tripod bearing assembly permits angular and axial displacement between the two
15 shafts during dynamic rotation of the assembly. Typically, a needle bearing is provided between each trunion and the outer member.

 The needle bearing of the prior art is generally assembled to the trunion in one of two manners
20 and particularly designed therefor. A first bearing type and assembly method is illustrated in Figure 1. The trunion supports a plurality of needles which support a roller which engages a branch of an outer member of a constant velocity joint. In the prior art assembly shown
25 in Figure 1, the needles bear directly on a bearing surface machined onto the trunion. An outer bearing is provided between the needles and the outer member (the outer member is not shown). The needles are therefore assembled between the trunion and the outer bearing.
30 Such an assembly requires a large amount of labor or specialized machinery to enable the assembly of the individual needles in this manner. It would therefore be desirable to provide an assembly in which the needles

were assembled in a subassembly prior to installation onto the trunion.

A second type of bearing is illustrated in Figures 2 and 3. This assembly includes a preassembled
5 needle bearing interposed between a trunion and outer member. The needles are assembled into a bearing assembly prior to installation of the bearing assembly onto a trunion.

The prior art assembly shown in Figures 2 and 3
10 includes a means for displacing the bearing assembly relative to the trunion. As illustrated in Figure 2, the displacement comprises an angular movement of the trunion relative to the inner race of the bearing assembly.

Figure 3 illustrates an alternate means for
15 displacing the bearing assembly relative to the trunion comprising an axial movement of the trunion relative to the inner race of the bearing assembly. These prior art configurations require a bearing provided between the trunion and the needle bearing and also require
20 additional machining of the trunion to permit the axial sliding movement. It would be desirable to provide a trunion assembly which includes needle bearings which are preassembled into a bearing assembly which is subsequently assembled onto the trunion, but which does
25 not require relative axial or rotational movement to the trunion, so machining of the trunion is minimized.

Summary of the Invention

30 In accordance with the objects of this invention, an improved tripod assembly is provided. The tripod bearing assembly includes a spider assembly with a trunion. A bearing assembly is press fit onto the

trunion. The bearing assembly has an inner race, an outer race, and a plurality of needle rollers to permit relative rotation between the inner and outer races. The bearing assembly is axially retained to the spider. The trunion therefore does not require machining and the bearing is preassembled prior to installation onto the trunion.

Brief Description of the Drawings

10

Figure 1 is an exploded view of a prior art trunion of a tripod bearing assembly.

Figure 2 is a partial side sectional view of an alternative prior art tripod bearing assembly.

15

Figure 3 is a partial end sectional view of the prior art tripod shown in Figure 2.

Figure 4 is a partial sectional view of a needle roller assembly being installed on a trunion according to the present invention.

20

Figure 5 is a partial sectional view of a needle roller assembly being installed on a trunion according to an alternative embodiment of the present invention.

25

Detailed Description of Preferred Embodiments

Figure 4 illustrates a tripod bearing assembly 10. The assembly 10 includes a spider 12 having three trunions 20 equally spaced. A bearing 40 is pressed fit onto the trunion 20. The bearing 40 includes an inner race 42 supporting a plurality of needles 46, and an outer race 48 supported by the needles 46. In a preferred embodiment, the inner race comprises a formed

cup, preferably formed by drawing the inner race to the necessary shape. The outer race 48 is rotatable relative to the inner race 42 on the needles 46.. The outer race 48 drivably engages an outer member (not shown) in a manner known to one skilled in the art.

The trunion 20 includes an outer diameter 30 which is sized to be press fit to the inner surface 44 of the inner bearing 40. The press fit of the bearing 40 to the trunion 20 and the inner race 42 eliminate the need for machining (such as turning or grinding) of the outer diameter 30 of the trunion 20, since it is not a bearing surface. Thus, the trunion may be assembled "as formed" without finish machining in this embodiment. The spider 12 could, for example, be forged, then have the bearing assemblies 40 press fit onto the trunions 20, then finally assembled into a constant velocity joint assembly for use in an automobile.

An undercut 52 is preferably formed on the trunion to further eliminate the need for any finish machining of the spider at this surface. The bearing 40 is axially restrained in a first direction by a shoulder 54 provided on the spider adjacent undercut 52. A snap ring groove 50 is provided at the distal end of the trunion 20 to engage a snap ring (not shown) to axially retain the bearing 40 to the spider 12 in the opposite direction. Thus, during operation of the joint 10, the bearing 40 is axially fixed to the trunion 20 between the snap ring groove 50 and the shoulder 54 without the need for finish machining. The press fit also aids in axially retaining the bearing 40 to the trunion 20.

The outer race 48 rotates circumferentially about the trunion 20. The outer member (not shown) is able to rotate or move axially relative to the outer race

48 in a manner known to one skilled in the art, similar to the manner described in U.S. patent 4,693,698, which is incorporated herein by reference. The tripod thus accommodates any angular deflection of the joint or
5 relative axial movement.

The bearing surface 30 of the trunion 20 comprises a cylinder. The engagement of this cylindrical trunion with the inner surface 44 of the bearing 40 prevents angular displacement therebetween.

10 In an alternative embodiment, as shown in Figure 5, a bearing assembly 60 is fit onto a spider 14. The spider includes three trunions 72 as described above with reference to Figure 4. Each trunion 72 includes a finished bearing surface 74. The needles 64 of the
15 bearing 60 rotate at 62 on the bearing surface 74 as an inner race in a manner similar to that described in the '698 patent. The bearing 60 includes a plurality of needles 64, an outer race 66, and a cage 68 to retain the needles 64 after assembly to the outer race 66, prior to
20 installation onto the trunion 72. Thus the bearing assembly 60 is shipped as a modular unit and pressed fit onto the trunion 14 in a simple manner, without the need to handle loose needles at the tripod assembly source. The cage is preferably made from a glass-filled polymer
25 as is known to one skilled in the art. The cage includes a plurality of pockets for retaining the needles to the outer race as is known to one skilled in the art. In an alternative embodiment, the cage is formed from steel.

In a manner similar to that described above
30 with reference to Figure 4, the bearing 60 is retained after assembly in a first axial direction by a shoulder 80 provided on the spider 14 adjacent trunion 72. An undercut 78 is provided on the trunion 72 to simplify

finish machining. A groove 76 is provided at the
opposite end of the trunion 72. A snap ring 77 is
installed in the groove 76 after the bearing 60 is
assembled to retain the bearing 60 in the second axial
5 direction. In this embodiment, the trunion preferably
includes a ground surface 74, since it is a bearing
surface. The cage 68 serves as an assembly aid to
prevent the need for assembling the needles at final
assembly of the joint, as the bearing 60 is shipped as an
10 assembly.

The above spider assembly has been describe
with reference to a constant velocity joint. However,
one skilled in the art recognizes that these concepts
maybe used in a universal joint.

15 It is to be understood that the embodiments of
the invention described above are merely illustrative of
application of principals of the present invention.
Numerous modifications maybe made to the methods and
apparatus described above without departing from the true
20 spirit and scope of the invention.

CLAIMS

What is claimed is:

- 5 1. A tripod bearing assembly comprising:
 a spider assembly having a trunion radially
projecting therefrom;
 a bearing assembly press fit onto the trunion,
the bearing assembly comprising an inner race, an outer
10 race, and a plurality of needle rollers interposed
therebetween to permit relative rotation between the
inner and outer race; and
 means for axially retaining the bearing
assembly to the spider.
- 15 2. A spider assembly according to claim 1,
further comprising said trunion having a non-machined
outer surface for press-fit engagement with the inner
race of the bearing assembly.
- 20 3. A spider assembly according to claim 2,
further comprising a means for angularly retaining the
bearing to the trunion.
- 25 4. A bearing assembly according to claim 3,
wherein the inner race comprises a formed cup.
5. A bearing assembly according to claim 4,
wherein the cup is formed by drawing.
- 30 6. A method of assembling a tripod bearing
assembly including a spider, comprising:
 forming a plurality of trunions on the spider;

press fitting a bearing assembly onto the
trunion, the bearing assembly comprising an inner race,
an outer race, and a plurality of rollers interposed
therebetween to permit relative rotation between the
5 inner and outer race; and

axially retaining the bearing assembly to the
spider.

7. A method according to claim 6, wherein the
10 trunion is forged and the bearing is press-fit onto the
trunion without machining the trunion.

8. A method according to claim 7, further
comprising the step of angularly retaining the bearing to
15 the trunion.

9. A method according to claim 8, further
comprising the step of drawing the inner race.

10. A tripod bearing assembly including a
20 spider, comprising:

a non-machined trunion radially provided on the
spider, the trunion comprising an undercut adjacent the
spider, a cylindrical surface, and a snap ring groove
25 axially spaced from the undercut;

a bearing assembly press-fit onto the trunion
between the spider and snap ring groove, the bearing
assembly comprising an inner race, an outer race, and a
plurality of needle rollers interposed therebetween to
30 permit relative rotation between the inner and outer
race; and

means for axially and angularly retaining the
bearing assembly to the spider.

11. A bearing assembly according to claim 10,
wherein the inner race comprises a formed cup.

12. A bearing assembly according to claim 11,
5 wherein the cup is formed by drawing.

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100




Figure 1

Prior Art




Figure 2

Prior Art




Figure 3

Prior Art




Figure 4




Figure 5

DECLARATION AND POWER OF ATTORNEY - ORIGINAL APPLICATION				Attorney's Docket No. 197-0216												
<p>As a below named inventor, I hereby declare: My residence, post office address and citizenship are as stated below next to my name:</p> <p>I verily believe I am the original, first and sole inventor or an original, first and joint inventor of the subject matter that is claimed and for which a patent is sought on the invention entitled</p> <p><i>Tripod Bearing Assembly</i></p> <p>the specification of which is attached hereto.</p> <p>I have reviewed and understand the contents of the specification identified above, including the claims.</p> <p>I acknowledge my duty to disclose information of which I am aware that is material to the examination of this application in accordance with Section 1.56(a), Title 37 of the Code of Federal Regulations; and</p> <p>as to application for patents or inventor's certificate on the invention filed in any country foreign to the United States of America, prior to this application by me or my legal representatives or assigns,</p> <p style="margin-left: 40px;"><input checked="" type="checkbox"/> no such applications have been filed, or</p> <p style="margin-left: 40px;"><input type="checkbox"/> such applications have been filed as follows:</p>																
COUNTRY	APPLICATION NO.	DATE OF FILING <small>(day, month, year)</small>	DATE OF ISSUE <small>(day, month, year)</small>	PRIORITY CLAIMED UNDER 35 USC 119												
<p>I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.</p> <table style="width: 100%; border-collapse: collapse;"><tr><td style="border-bottom: 1px solid black; width: 33%;"></td><td style="border-bottom: 1px solid black; width: 33%;"></td><td style="border-bottom: 1px solid black; width: 33%;"></td></tr><tr><td style="text-align: center; font-size: small;">(Application Number)</td><td style="text-align: center; font-size: small;">(Filing Date)</td><td style="text-align: center; font-size: small;">(Status - patented, pending, abandoned)</td></tr><tr><td style="border-bottom: 1px solid black;"></td><td style="border-bottom: 1px solid black;"></td><td style="border-bottom: 1px solid black;"></td></tr><tr><td style="text-align: center; font-size: small;">(Application Number)</td><td style="text-align: center; font-size: small;">(Filing Date)</td><td style="text-align: center; font-size: small;">(Status - patented, pending, abandoned)</td></tr></table>								(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)				(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)
(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)														
(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)														
<p>POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the United States Patent and Trademark Office connected therewith and to act on my behalf before the competent International Authorities in connection with any and all international applications filed by me.</p> <p>(List name and registration number)</p> <p>James J. Donavio - 40,360 Frank G. McKenzie - 29,242 Roger L. May - 26,406</p>																

Address all correspondence and telephone calls to:

James J. Dottavio
Ford Global Technologies, Inc.
One Parklane Boulevard
911 East Parklane Towers
Dearborn, Michigan 48126

Telephone: (313) 323-2046

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Name, residence, and post office address of inventor:

Citizenship: US

Robert W. Sams
43506 Herring
Clinton Twp, MI 48038

Inventor's signature



Date

16 Dec 97

Name, residence, and post office address of inventor:

Citizenship: US

Richard Seidel
48558 Declaration
Macomb Township, MI 48044-0182

Inventor's signature



Date

16 Dec 97

Name, residence, and post office address of inventor:

Citizenship: US

Michael Walter Hapson
43844 Leelanau Trail
Clinton Twp, MI 48088

Inventor's signature



Date

17 Dec 97